# UNDERLAYMENTS



The perfect finish for any floor

## 6 MIL POLY MOISTUREBARRIER FOR LAMINATE AND RESILIENT/VINYL FLOORS

### **EASY TO SELL**

When customers purchase new floors, now it's easy to offer them 6 mil poly MoistureBarrier to complete their projects.

#### MoistureBarrier Underlayment


- Works with pad-attached products
- Enhances the floor's locking system
- Offers superior sound control




## **EASY TO INSTALL**

#### Installation is as easy as 1, 2, 3.


1. Unroll the first row of underlayment parallel to the laying direction of the floor with the moisture barrier face down against the subfloor, allowing the pad to run up the walls 1 to 2 inches.



2. Roll out the second row next to the first. Butt together tightly, covering the overlapping moisture barrier lip.



3. Remove the tape liner from the second row and secure it to the overlapping moisture barrier. Press firmly to ensure a tight bond.



## **ORDER INFO**



Inventory Style Number	In Wide/Pc	In Long/Pc	Sq Ft	Thickness	Core Material	Surface Materials
VU40	46"	316"	100 sq ft	6 mil	Polyethylene	Polyethylene
VU41	46"	104.4"	400 sq ft	6 mil	Polyethylene	Polyethylene







The perfect finish for any floor.

#### **MOISTURE BARRIER**

UNDERLAYMENT FOR LAMINATE AND VINYL FLOORING

Moisture Barrier underlayment is the standard in basic moisture protection.

- Meets moisture requirements
- Easy installation
- Lavs flat

Thickness

Moisture Protection .01 grains/1hr/ft<sup>2</sup>

> Size 400 sq ft (46" x 104.4')

Safety Idorless Nontoxic



